

Specification Data Sheet | Model: 10TCC-EU(W)



**TRANSCUBE CONTRACT 880 Ltr**

UN (United Nations) IBC Intermediate Bulk Container, approved for transport of diesel fuel under the ADR Regulations. The Transcube Global is fully banded steel in steel (to ensure environmental compliance with Pollution Prevention Guidelines (PPG2)).

- ❖ 850 litre model can be transported full of diesel without the need for ADR Driver Training.
- ❖ Easily stacked 2 high full, 3 high empty to reduce storage space requirements.
- ❖ Full load lifting eyes, forklift pockets and internal baffles designed to allow handling of the TransCube Contract full of fuel.
- ❖ Secure lockable access hatch to house pumps (electric and hand), and feed and return connections for up to 1 generator.
- ❖ Size to stack inside shipping containers and across truck beds providing economical transportation.
- ❖ Protective galvanised stack/lifting corner plates preventing damage to tank paintwork and decals..

SPECIFICATION			
Standard Tank Fittings: 1 x 2" Fill Point : 1 x 2" Vent Fill : Dipstick Tank Gauge : Pressure / Vacuum Vent : Breather Vent : 1 x 1" Pump & Auxiliary Feed : 1 x 1/2" Return : Pump Bracket			
Capacity (Brim Full) Litres:	880	Weight Unladen (kg):	370
Capacity (Brim Full) Gallons:	193	Weight Laden (kg):	1270*
Dimensions Length (mm):	1150	Bund Material (thickness):	S235 (2mm)
Dimensions Width (mm):	1150	Inner Tank Material (thickness):	S235 (2mm)
Dimensions Height (mm)	1320	Design Approvals:	UN IBC Type 31A
Cabinet Dimensions:	To suit standard pumping equipment	Design Standards:	Banded to COP Regulations (PPG2)
Notes			
* Specific gravity of diesel taken as 0.9 for this calculation			

Revision Date: 07/01/2016

