



Image shown may not reflect actual package.

STANDBY 720 e kW 900 kVA 50 Hz 1500 rpm 400 Volts

Caterpillar is leading the power generation marketplace with Power Solutions engineered to deliver unmatched flexibility, expandability, reliability, and cost-effectiveness.

FEATURES

FUEL/EMISSIONS STRATEGY

- Low Fuel consumption

FULL RANGE OF ATTACHMENTS

- Wide range of bolt-on system expansion attachments, factory designed and tested
- Flexible packaging options for easy and cost effective installation

SINGLE-SOURCE SUPPLIER

- Fully prototype tested with certified torsional vibration analysis available

WORLDWIDE PRODUCT SUPPORT

- Cat dealers provide extensive post sale support including maintenance and repair agreements
- Cat dealers have over 1,800 dealer branch stores operating in 200 countries
- The Cat® S•O•SSM program cost effectively detects internal engine component condition, even the presence of unwanted fluids and combustion by-products

CAT® 3412C TA DIESEL ENGINE

- Reliable, rugged, durable design
- Field-proven in thousands of applications worldwide
- Four-stroke-cycle diesel engine combines consistent performance and excellent fuel economy with minimum weight

CAT GENERATOR

- Designed to match the performance and output characteristics of Cat diesel engines
- Single point access to accessory connections
- UL 1446 recognized Class H insulation

CAT EMCP 4 CONTROL PANELS

- Simple user friendly interface and navigation
- Scalable system to meet a wide range of customer needs
- Integrated Control System and Communications Gateway

STANDBY 720 ekW 900 kVA

50 Hz 1500 rpm 400 Volts

FACTORY INSTALLED STANDARD & OPTIONAL EQUIPMENT

System	Standard	Optional
Air Inlet	<ul style="list-style-type: none"> • Single element canister type air cleaner • Service indicator 	<input type="checkbox"/> Dual element air cleaner <input type="checkbox"/> Heavy-duty air cleaner
Cooling	<ul style="list-style-type: none"> • Radiator with guard • Coolant drain line with valve • Fan and belt guards • Cat® Extended Life Coolant • Low coolant level alarm or shutdown 	<input type="checkbox"/> Radiator duct flange <input type="checkbox"/> Jacket water heater with shutoff valve <input type="checkbox"/> Heat exchanger and expansion tank
Exhaust	<ul style="list-style-type: none"> • Stainless steel exhaust flex and ANSI style outlet flange, gasket, bolts and mating weld flange, shipped loose 	<input type="checkbox"/> Mufflers (10 or 35 dBA) <input type="checkbox"/> Elbow kit and through-wall installation kit <input type="checkbox"/> Manifold and turbocharger guards
Fuel	<ul style="list-style-type: none"> • Primary and secondary fuel filters • Water separator • Fuel priming pump • Flexible fuel lines 	<input type="checkbox"/> Manual transfer pump <input type="checkbox"/> Choice of three Automatic Transfer Systems
Generator	<ul style="list-style-type: none"> • Class H insulation • Class F temperature rise • VR6 Voltage Regulator, 3-phase sensing, 2:1 Volts/Hz • Reactive droop • Extension box • Bus bar connection • Segregated low voltage (AC/DC) wiring panel 	<input type="checkbox"/> Digital Voltage Regulator with kVAR/PF control <input type="checkbox"/> Anti-condensation space heater <input type="checkbox"/> Oversize and premium generators <input type="checkbox"/> Circuit breakers, IEC Compliant, 3-pole or 4-pole with shunt trip
Governor	<ul style="list-style-type: none"> • PEEC - Cat Electronic 	<input type="checkbox"/> Electronic load sharing
Control Panels	<ul style="list-style-type: none"> • 4.2 (mounted inside power center) • Rear facing • Speed adjust • Emergency stop pushbutton • Voltage adjustment 	<input type="checkbox"/> Right-hand mounting of control panel <input type="checkbox"/> Local annunciator modules (NFPA 99/110) <input type="checkbox"/> Remote annunciator modules (NFPA 99/110) <input type="checkbox"/> Discrete I/O module
Lube	<ul style="list-style-type: none"> • Lubricating oil and filter • Oil drain line with valves • Fumes disposal 	<input type="checkbox"/> Manual sump pump
Mounting	<ul style="list-style-type: none"> • Formed steel base • Linear vibration isolators between base and engine-generator 	<input type="checkbox"/> Integral fuel tank base <input type="checkbox"/> Sub base fuel tank <input type="checkbox"/> Wide base <input type="checkbox"/> Skid base
Starting/Charging	<ul style="list-style-type: none"> • 45 amp charging alternator • Fuel shutoff solenoid • 24 volt starting motor • Battery with rack and cables 	<input type="checkbox"/> Heavy-duty starting system <input type="checkbox"/> 5 or 10 amp battery charger <input type="checkbox"/> Oversize batteries <input type="checkbox"/> Ether starting aid <input type="checkbox"/> Battery disconnect switch
General		<input type="checkbox"/> Enclosures - sound attenuated, weather protective <input type="checkbox"/> Automatic transfer switches (ATS) <input type="checkbox"/> Floor standing circuit breakers <input type="checkbox"/> EU Certificate of Conformance (CE)

STANDBY 720 ekW 900 kVA

50 Hz 1500 rpm 400 Volts

SPECIFICATIONS

CAT GENERATOR

Frame size.....	598
Excitation.....	Self Excitation
Pitch.....	0.8667
Number of poles.....	4
Number of bearings.....	Single bearing
Number of Leads.....	012
Insulation.....	UL 1446 Recognized Class H with tropicalization and antiabrasion - Consult your Caterpillar dealer for available voltages
IP Rating.....	Drip Proof IP22
Alignment.....	Pilot Shaft
Overspeed capability.....	180
Wave form Deviation (Line to Line).....	Less than 5% deviation
Voltage regulation.....	Less than +/- 1/2% (steady state) Less than +/- 1% (no load to full load)
Telephone influence factor.....	Less than 50
Harmonic Distortion.....	Less than 5%

CAT DIESEL ENGINE

3412C TA, V-12, 4-Stroke Water-cooled Diesel	
Bore.....	137.20 mm (5.4 in)
Stroke.....	152.40 mm (6.0 in)
Displacement.....	27.02 L (1648.86 in ³)
Compression Ratio.....	13.0:1
Aspiration.....	TA
Fuel System.....	Pump and Lines
Governor Type.....	PEEC - Cat Electronic

CAT EMCP 4 SERIES CONTROLS

EMCP 4 controls including:

- Run / Auto / Stop Control
- Speed and Voltage Adjust
- Engine Cycle Crank
- 24-volt DC operation
- Environmental sealed front face
- Text alarm/event descriptions

Digital indication for:

- RPM
- DC volts
- Operating hours
- Oil pressure (psi, kPa or bar)
- Coolant temperature
- Volts (L-L & L-N), frequency (Hz)
- Amps (per phase & average)
- ekW, kVA, kVAR, kW-hr, %kW, PF

Warning/shutdown with common LED indication of:

- Low oil pressure
- High coolant temperature
- Overspeed
- Emergency stop
- Failure to start (overcrank)
- Low coolant temperature
- Low coolant level

Programmable protective relaying functions:

- Generator phase sequence
- Over/Under voltage (27/59)
- Over/Under Frequency (81 o/u)
- Reverse Power (kW) (32)
- Reverse reactive power (kVA) (32RV)
- Overcurrent (50/51)

Communications:

- Six digital inputs (4.2 only)
- Four relay outputs (Form A)
- Two relay outputs (Form C)
- Two digital outputs
- Customer data link (Modbus RTU)
- Accessory module data link
- Serial annunciator module data link
- Emergency stop pushbutton

Compatible with the following:

- Digital I/O module
- Local Annunciator
- Remote CAN annunciator
- Remote serial annunciator

STANDBY 720 ekW 900 kVA

50 Hz 1500 rpm 400 Volts

TECHNICAL DATA

Open Generator Set - - 1500 rpm/50 Hz/400 Volts	DM1909	
Package Performance Genset Power rating @ 0.8 pf Genset Power rating with fan	900 kVA 720 ekW	
Fuel Consumption 100% load with fan 75% load with fan 50% load with fan	191.7 L/hr 143.7 L/hr 99.6 L/hr	50.6 Gal/hr 38.0 Gal/hr 26.3 Gal/hr
Cooling System¹ Air flow restriction (system) Air flow (max @ rated speed for radiator arrangement) Engine coolant capacity Radiator coolant capacity Engine Coolant capacity with radiator/exp. tank	0.12 kPa 1176 m ³ /min 59.0 L 90.0 L 149.0 L	0.48 in. water 41530 cfm 15.6 gal 23.8 gal 39.4 gal
Exhaust System Combustion air inlet flow rate Exhaust stack gas temperature Exhaust gas flow rate Exhaust flange size (internal diameter) Exhaust system backpressure (maximum allowable)	54.7 m ³ /min 544.9 °C 157.3 m ³ /min 203.2 mm 6.7 kPa	1931.7 cfm 1012.8 °F 5555.0 cfm 8.0 in 26.9 in. water
Heat rejection Heat rejection to coolant (total) Heat rejection to exhaust (total) Heat rejection to atmosphere from engine Heat rejection to atmosphere from generator	429 kW 721 kW 119 kW 33.9 kW	24397 Btu/min 41003 Btu/min 6768 Btu/min 1927.9 Btu/min
Alternator² Motor starting capability @ 30% voltage dip Frame Temperature Rise	1629 skVA 598 130 °C	234 °F
Lube System Sump refill with filter	139.0 L	36.7 gal
Emissions³ NOx mg/nm ³ CO mg/nm ³ HC mg/nm ³ PM mg/nm ³	2954.8 mg/nm ³ 454.4 mg/nm ³ 143.1 mg/nm ³ 64.8 mg/nm ³	

¹ For ambient and altitude capabilities consult your Cat dealer. Air flow restriction (system) is added to existing restriction from factory.

² UL 2200 Listed packages may have oversized generators with a different temperature rise and motor starting characteristics. Generator temperature rise is based on a 40°C ambient per NEMA MG1-32.

³ Emissions data measurement procedures are consistent with those described in EPA CFR 40 Part 89, Subpart D & E and ISO8178-1 for measuring HC, CO, PM, NOx. Data shown is based on steady state operating conditions of 77°F, 28.42 in HG and number 2 diesel fuel with 35° API and LHV of 18,390 btu/lb. The nominal emissions data shown is subject to instrumentation, measurement, facility and engine to engine variations. Emissions data is based on 100% load and thus cannot be used to compare to EPA regulations which use values based on a weighted cycle.

STANDBY 720 ekW 900 kVA

50 Hz 1500 rpm 400 Volts

RATING DEFINITIONS AND CONDITIONS

Meets or Exceeds International Specifications: AS1359, CSA, IEC60034-1, ISO3046, ISO8528, NEMA MG 1-22, NEMA MG 1-33, UL508A, 72/23/EEC, 98/37/EC, 2004/108/EC

Standby - Output available with varying load for the duration of the interruption of the normal source power. Average power output is 70% of the standby power rating. Typical operation is 200 hours per year, with maximum expected usage of 500 hours per year. Standby power in accordance with ISO8528. Fuel stop power in accordance with ISO3046. Standby ambients shown indicate ambient temperature at 100% load which results in a coolant top tank temperature just below the shutdown temperature.

Ratings are based on SAE J1349 standard conditions. These ratings also apply at ISO3046 standard conditions. **Fuel rates** are based on fuel oil of 35° API [16° C (60° F)] gravity having an LHV of 42 780 kJ/kg (18,390 Btu/lb) when used at 29° C (85° F) and weighing 838.9 g/liter (7.001 lbs/U.S. gal.). Additional ratings may be available for specific customer requirements, contact your Cat representative for details. For information regarding Low Sulfur fuel and Biodiesel capability, please consult your Cat dealer.

STANDBY 720 ekW 900 kVA

50 Hz 1500 rpm 400 Volts

DIMENSIONS

Package Dimensions		
Length	4485.0 mm	176.57 in
Width	1741.6 mm	68.57 in
Height	1986.7 mm	78.22 in
Weight	5748 kg	12,672 lb

Advanced Diesel Engineering
14 Langthwaite Business Park
South Kirkby, Pontefract
WF9 3AP, UK
Telephone: +44 (0) 1977 658 100
Fax: +44 (0) 1977 608 111
E-mail: enquiries@adeltd.co.uk
Web: www.adeltd.co.uk